

STANDARD FEATURES

| |
|--|
| Platform Available in Aluminum or Steel |
| Consolidated Tilt & Full Length Mounting Frame |
| Full Length Nylatron Slide Pads |
| Two 3" Lift Cylinders |
| One Extension Cylinder |
| Right and Left Front Chain Trays |
| Front and Rear Tie Down Slots |
| Positive Bed Lock Down System |
| Bed Anti-Tilt Feature |
| Adjustable Landing Legs |
| Removable Side Rails (15 Series Steel) |
| Solid Tube Side Rails (Aluminum and 10 Series Steel) |
| 8,000 lb. Hydraulic Winch with 50' of Cable |
| Winch Clutch Release |
| Winch Roller Guides |
| Winch Cable Tensioner |
| Left and Right Hand Illuminated Controls |
| Back Up Lights |
| Federal Standard 108 Lighting |
| Back Up Alarm |
| Hydraulic Independent Wheel Lift System with Slide-In L-Arms |
| Wheel Lift Safety Pin |
| Safety Chains |
| Century Mud Flaps |
| Hydraulic Pump |
| Full Height Steel Headboard |
| Steel Beds Painted in Black Acrylic Urethane |
| Pre-Assembled and Factory Tested |

OPTIONAL FEATURES

| |
|---|
| PTO |
| Galvanized Subframe |
| Optional Steel or Aluminum Tool Compartments |
| Switch Panel |
| Light Bar |
| Work Lights (Rear or Winch Mounted) |
| Spotlights (Directional) |
| Various Chain & Strap Assemblies |
| Additional Key Slots |
| Removable Tube Side Rails (N/A on Right Approach) |
| Removable Blade Side Rails (N/A on Right Approach) |
| Aluminum Overlay Side Rails (Steel Only, N/A on Right Approach) |
| Smooth Floor instead of Diamond Plate (Steel Only) |
| Apitong Wood Floor (N/A on Right Approach) |
| Additional Cross Members (Steel Only) |
| Optional Colors, Top of Deck & Removable Rails (Steel Only) |
| Right Approach Option (Steel 10 Series Only) |
| Body Built 102" Wide |
| 3-Way Pivoting L-Arm System |
| Dock Stabilizer in lieu of Wheel Lift |
| Side Mount Winch |
| Planetary Winch in lieu of Worm Gear Winch |
| 10,000 lb. or 12,000 lb. Winch |
| Lanyard Control for Winch |
| Stationary Headboard |
| Factory Installation |
| Many other Popular Century Carrier Options |

BED

| SPECIFICATIONS | 10 SERIES | 15 SERIES |
|---------------------------|--------------------------|-------------------------------|
| Platform Length | 19', 19'6", 21', & 22' | 19', 21', & 22' |
| Load Rating | *10,000 lbs. | *15,000 lbs. |
| Platform Thickness | 3/16" Aluminum or Steel | 3/16" Aluminum or Steel |
| Steel Crossmembers | 2" x 2" on 8" Centers | 2 1/2" x 2 1/2" on 8" Centers |
| Aluminum Crossmembers | 2 5/16" on 4" Centers | 3" on 4" Centers |
| Overall Width | 96" | 96" |
| Inside Width | 91.5" | 91.5" |
| Controls | 5 Spool Mono-block Valve | 5 Spool Mono-block Valve |
| Winch Rating (1st Layer) | 8,000 lb. | 8,000 lb. |
| Cable Diameter and Length | 3/8" x 50' | 3/8" x 50' |

* Platform rating is based on equally distributed load.

WHEEL-LIFT SPECIFICATIONS

| | | |
|-------------------------------|---|------------|
| Lift Rating at Full Extension | 3,000 lbs. (2,000 lbs. for under 19,000 GVW) | 3,500 lbs. |
| Tow Rating at Full Extension | 6,250 lbs. (5,000 lbs. for under 19,000 GVW) | 6,250 lbs. |

TRUCK RECOMMENDATIONS

| | | |
|--|-------------|--------|
| Minimum GVW | 15,000 | 25,500 |
| Maximum GVW | 25,500 | 28,000 |
| Recommended Tire Size | 16" - 19.5" | 22.5" |
| Minimum Height from Ground to Top of Frame | 34" | 40" |
| Maximum Height from Ground to Top of Frame | 39" | 44" |

RECOMMENDED CAB TO AXLE (C.A.)

| | |
|-------|------|
| 19' | 120" |
| 19'6" | 127" |
| 21' | 144" |
| 22' | 156" |

NOTE: Specifications subject to change without notice. All ratings are based on structural factors only, not vehicle capacities or capabilities.

CENTURY®

8503 Hilltop Drive • Ooltewah, TN 37363
 800-292-0330 • 423-238-4171
 FAX 423-238-5371 • www.MILLERIND.com

DISTRIBUTED BY:

Jeff Ingram Wrecker Sales Inc..
 Horn Lake, MS 38637
 PHONE (662) 280-6761
 (866) 280-6761