

# Century – Super Duty Industrial Carrier

## STANDARD FEATURES

- Hydraulic Dock Stabilizer
- Dual Lighted Controls
- Tilt Lockout Controls
- Positive Lock Down System
- Drivers & Passenger Side Chain Trays
- 12 Key Holes (4 Per Side, 4 Across Rear)
- Consolidated Tilt Frame & Mounting Frame
- Two Power Lift Cylinders
- One Extension Cylinder
- 20,000 lbs. Planetary Winch with Cable
- Mud Flaps
- Air Winch Release
- Federal 108 Light Group
- Steel Tube Cab Protector
- Pump
- Painted in Black Acrylic Enamel
- All Components for Complete Installation

## OPTIONAL EQUIPMENT

- Air Shift PTO
- Tool Compartment with Locking Latch
- Four Piece Removable Side Rails
- 102" Wide Deck
- Smooth Floor in Lieu of Diamond Plate
- Light Bar
- Apitong Wood Floor
- Tie Down Chains
- Working Area Lighting
- Additional Key Slots
- Dual Key Slots Down Center or Outside of Deck
- 1/4" Floor Deck in Smooth or Diamond Plate
- Winch Cable Tensioner
- Rub Rail with Outside Stake Pockets & Pipe Spools
- Many Other Popular Century Options
- Drop Wheel Wells on Deck



## BED SPECIFICATIONS

Load Rating:	30,000 lbs.*
Platform Length:	24', 26', 28' or 30'
Platform Width:	102"
Platform Thickness:	3/16" CKD Floor
Platform Main Beams:	8" I-Beam
Platform Cross-Members:	2" x 4" x 1/8" Tubes on 6" Centers
Platform Sides:	7" x 4" x 3/8" Angle w/24" c/c Pockets
Rear Approach Plate:	Wedge Tip
Sub-Frame:	7" x 4" x 3/8" Tube
Rear Pivot:	1 Piece – 2" Diameter
Winch: Rating (1 <sup>st</sup> Layer)	20,000 lbs. Planetary
Cable Diameter & Length:	9/16" x 100'
Power Lift Cylinders:	5" x 32" Stroke
Extension Cylinder:	5" x 120" Stroke
* The Ratings Specified are Based on Structural Factors Only – Not Vehicle Capacity. Platform Rating is Based on Equally Distributed Load.	

## CHASSIS RECOMMENDATIONS

Tandem Axle Chassis		
Minimum G.V.W.R. (Gross Vehicle Weight Rating)		50,000 lbs.
Minimum C.B. (Cab to Bogie)	Dimension 24'	142"
	Dimension 26'	166"
	Dimension 28'	190"
	Dimension 30'	214"
Minimum Frame R.B.M. (Each Rail)		3 Million Inch lbs.
Note: Specifications subject to change without notice. All ratings specified are based on structural factors only, not vehicle capacities, or capabilities.		



NOTE: Some optional equipment may be shown. Other Century towing and recovery equipment is available from your local Century Distributor.



8503 Hilltop Drive  
Ooltewah, TN 37363  
PHONE (423) 238-4171  
(800) 292-0330  
FAX (423) 238-5371

### DISTRIBUTED BY:

**Jeff Ingram Wrecker Sales Inc.**  
Horn Lake, MS 38637  
PHONE (662) 280-6761  
(866) 280-6761